


Shield's Gear Oil SAE 85W140 is a multipurpose, extreme pressure, multigrade gear oil. It exceeds the performance requirements of leading OEMs, truck and gear box manufacturers. The oil is an all-year-round gear oil which ensures full and immediate lubrication at cold starts and with a minimum associated power loss. The gear oil provides a supreme performance in passenger cars and trucks operating in both on-road & off-road conditions and at very high temperature conditions.



### PERFORMANCE LEVELS:

- API GL-5, GL-4, GL-1
- MIL-L-2105
- ZF, Fuller & CS 3000A
- MACK Go-G Specifications

### APPLICATIONS:

It is appropriate for hypoid, spiral bevel final drives and limited slip axles operating under severe load and high torque cycles. This oil is most suitable for manual transmissions, intermediate gear boxes, manual steering gear box drives, differentials (including limited-slip ones), and power take-offs found on motor vehicles and commercial machinery.

### TYPICAL PHYSICAL PROPERTIES

SL#	Characteristics Unit	Test Method	GL-1	GL-4	GL-5
1	Density @ 15°C	ASTM D 1298	0.8970	0.8970	0.8970
2	Viscosity @ 40°C	ASTM D 445	350	350	350
3	Viscosity @ 100°C	ASTM D 445	29	29	29
4	Viscosity Index	ASTM D 445	113	113	113
5	Flash Point COC, °C	ASTM D 92	230	230	230
6	Pour Point, °C	ASTM D 97	-15	-15	-15
7	Color	ASTM D 1500	L1.5	L1.5	L1.5
8	Appearance	ASTM D 4176	C & B	C & B	C & B

\* Exact specifications may slightly vary from the above, but within the international standards